with accents



Delivering design options to put lighting where it's needed.

The Linea family is expertly crafted to drive design scenarios while seamlessly providing the freedom to create truly dynamic spaces. A synthesis of aesthetics, performance and energy efficiency, Linea delivers on its promises. Like the rest of the product family, the four new Linea solutions provide design options to spaces that require elegance and beauty while delivering real energy and maintenance savings. The four new solutions offer surface mount adjustable accents or flush mounted downlight to suit any design.














Linea 1.5" with Accent



Linea 2.5" with Accent





Application:

Commercial, Retail

LINEA® 1.5" DIRECT LED

WITH ADJUSTABLE ACCENTS

Mounting: Cable Suspended or Surface Direct **Wattages/Foot (Linear):** 5, 10 **(Accent):** 7

Lumen Output (Linear): Up to 3,263 (Accent): Up to 451

Color Temp: 2700K, 3000K, 3500K, 4000K

Dimming: 0-10V, 1% dimming; DALI dimming, 1% dimming

Accent Heads: Surface Mount; 1, 2 per side

LINEA® 1.5" DIRECT/INDIRECT LED

WITH ADJUSTABLE ACCENTS

Optics: Direct/Indirect; Lens, Louver Down/Batwing, Clear Lens Up

Wattages/Foot (Linear): 5, 10 (Accent): 7

Lumen Output (Linear): Up to 3,991 (Accent): Up to 451

Color Temp: 2700K, 3000K, 3500K, 4000K

Dimming: 0-10V, 1% dimming; DALI dimming, 1% dimming

Accent Heads: Surface Mount; 1, 2 per side

LINEA® 2.5" DIRECT LED

WITH ADJUSTABLE ACCENTS

Mounting: Cable Suspended or Surface Direct **Wattages/Foot (Linear):** 5, 10 **(Accent):** 7

Lumen Output (Linear): Up to 3,873 (Accent): Up to 451

Color Temp: 2700K, 3000K, 3500K, 4000K

Dimming: 0-10V, 1% dimming; DALI dimming, 1% dimming

Accent Heads: Surface, Flush Mount; 1, 2 per side

LINEA® 2.5" DIRECT/INDIRECT LED

WITH ADJUSTABLE ACCENTS

Optics: Direct/Indirect; Lens Down/Batwing, Clear Lens Up

Wattages/Foot (Linear): 5, 10 (Accent): 7

Lumen Output (Linear): Up to 3,991 **(Accent):** Up to 451

Color Temp: 2700K, 3000K, 3500K, 4000K

Dimming: 0-10V, 1% dimming; DALI dimming, 1% dimming

Accent Heads: Surface, Flush Mount; 1, 2 per side

For most updated performance and ordering information visit us at **amerlux.com**.

© 2020 Amerlux, LLC



178 Bauer Drive Oakland, New Jersey 07436 USA 973.882.5010 | Fax 973.882.2605

China Office

Oxidated Carpark 2nd Floor No. 124 Donghuan Road, Donghuan Jie Panyu, Guangzhou PRC 511400