



## ROOK FAMILY



**ROOK 350**



**ROOK 475**

### **CONTROL & OUTPUT, HANG IN BALANCE.**

The Rook family, a line that translates the control, performance and comfort of our downlights into a sophisticated new format. Offered in 3.5" and 4.75" apertures, these pendants pair with the Hornet HP Downlights and Evoke 4.75" Downlights. The Rook is the right choice for creating drama with focused light in reception areas, offices and retail environments.

## Application: Retail, Commercial, Hospitality, Supermarket

### Rook 350

**Open or Lensed Aperture**

**Aperture:** 3.5"

**Wattages:** 16, 18 (Open)  
14, 21 (Lensed)

**Delivered Lumens :** Up to 1,645

**CBCP:** Up to 12,508

**Binning:** 3 MacAdam

**Color Temp:** 2200K-4000K

**CRI:** 83 typ. & 90+ typ.

**Dimming:** ELV/TRIAC (standard),  
Lutron Hi-Lume, 0-10V

**Beam Spreads:** 15°-75°, Wall Wash

**Mounting:** Canopy/Cord, Rigid Stem,  
Surface, Conduit Mount

**Housing Finish:** MW, MB, SLV

**Aperture Finish:** MW, MB, SLV

**Configurations:** Intergral Driver (11.5")  
Remote Driver (6.5")

### Rook 475

**Open or Lensed Aperture**

**Aperture:** 4.75"

**Wattages:** 14, 19, 27

**Delivered Lumens:** Up to 2,104

**CBCP:** Up to 15,930

**Binning:** 3 MacAdam

**Color Temp:** 2200K-4000K

**CRI:** 83 typ. & 90+ typ.

**Dimming:** ELV/TRIAC (standard),  
Lutron Hi-Lume, 0-10V

**Beam Spreads:** 15°-75°, Wall Wash

**Mounting:** Canopy/Cord, Rigid Stem,  
Surface, Conduit Mount

**Housing Finish:** MW, MB, SLV

**Aperture Finish:** Semi-Diffuse  
Specular Clear (Lensed)

**Configurations:** Intergral Driver (12")

*For most updated performance and ordering information visit us at [amerlux.com](http://amerlux.com).*



3450 South Sam Houston Pkwy. E., Suite 400  
Houston, TX 77047 USA  
T: 281.997.5400 | F: 281.997.5441

**Headquarters**  
178 Bauer Drive, Oakland, NJ 07436 USA  
T: 973.882.5010 | F: 973.882.2605  
[amerlux.com](http://amerlux.com)  
© 2018 Amerlux, LLC

Oxidated Carpark 2nd Floor  
No.124 Donghuan Road, Donghuan Jie  
Panyu, Guangzhou PRC 511400