

# Varieta

## Two COB LED Flood Light



FLC2.x.x.BLK



### Features



The Amerlux Varieta flood luminaire employs solid state technology and precision engineering to provide LED solutions for exterior signage, wall washing, and landscape layouts. All components are encapsulated inside a single attractive enclosure designed for superior performance in weather resistant applications. Offered in a choice of finishes, and color temperatures, three mounting options and glare shield are also available.

### Product Overview

Type:	Exterior Flood Lighting
Wattage:	51W
Lumen Output :	5,200 lm
Color Temp:	3000K, 4000K, 5000K
Dimming:	0-10V

### PROJECT:

**PRODUCT DISCONTINUED**



#### Application:

Exterior flood lighting for signage, wall washing, and landscape layouts.

#### Construction:

- Die-cast aluminum faceplate
- Extruded aluminum housing
- IP67 sealed optical module

#### Optics:

- Lumen maintenance: 70% @ 50,000 hours
- Two COB LEDs available in various color temperatures
- Lens provides NEMA 7x6 distribution pattern

#### Electrical:

- Integral driver
- Input voltage 120V-277V auto-sensing
- Power consumption 51W
- 1/2" NPT wire entry
- 0-10V dimming is standard

ETL listed, suitable for wet locations.

#### Mounting:

- Cast aluminum pivot
- 180° tilt, 360° rotation

#### Mounting Accessories:

- GSP17 - Ground Stake
- PMBS-2-18 - Pole Mount
- WMS14 - Wall Mount

#### Accessories:

- EGS - External Glare Shield

#### Finish:

Premium quality thermoset polyester powdercoat for a durable finish.

#### Ambient Operating Range:

-30°C to 40°C

#### Weight:

11 lbs

#### EPA:

0.47



5 year limited warranty  
AMERLUX LED



# Varieta

Two COB LED Flood Light



## PROJECT:

## TYPE:

### Luminaire Ordering Information

FLC2

1

2

3

4

1

Model  
FLC2

2

Color Temp  
30 - 3000K  
40 - 4000K  
50\* - 5000K  
\* DLC listed

3

Finish  
BLK - Satin Black  
CLB - Classic Bronze  
GRN - Green  
TBK - Textured Black  
WHT - White  
CSTM - Custom

4

Accessories  
EGS - External Glare Shield

### Mounting Accessories Ordering Information (order separately)

1

2

1

Mounting Accessories  
GSP17 - Ground Stake (black polycarbonate)  
PMBS-2-18 - Pole Mount (finish matches fixture finish)  
WMS14 - Wall Mount (finish matches fixture finish)  
JBOX - Junction Box (finish matches fixture finish)  
JCOV - Junction Mount (finish matches fixture finish)

2

Finish  
BLK - Satin Black  
CLB - Classic Bronze  
GRN - Green  
TBK - Textured Black  
WHT - White  
CSTM - Custom


# Varieta

Two COB LED Flood Light

## PROJECT:


## TYPE:

### Accessories




**EGS**  
(External Glare Shield)

### Mounting



### Mounting Accessories (order separately)

#### Wall Mount




**WMS14**

Mounting hardware not included

**EPA: 0.208**


#### Pole Mount



**PMBS-2-18**


**EPA: 0.513**

#### Ground Spike



**GSP17**

### Optical Performance - Polar Graph



Maximum Candela = 3014  
Located at Horizontal Angle = -1, Vertical Angle = 1  
H - Horizontal Axial Candela  
V - Vertical Axial Candela

### Performance Chart

CCT	CRI	Approx. Lumens	Total Efficacy
<b>30</b> (3000K)	80	4,520	88 lm/W
<b>40</b> (4000K)	80	5,000	98 lm/W
<b>50</b> (5000K)	80	5,200	102 lm/W