


PROJECT:

Features

The Linea® 3.5" Direct LED ambient system is a small-scale 3.5" extruded profile that provides well-controlled ambient lighting. Engineered around the latest LED, in a choice of 5W/ft or 10W/ft LED boards. Excellent for commercial and retail ambient applications. Downlight component available with acrylic lens or parabolic louver options.



Product Overview

Type: Cable Suspended or Wall Mounted Linear, Direct/Indirect

Wattage: 5W/ft, 10W/ft (other wattages available see p2)

Color Temp: 2700K, 3000K, 3500K, 4000K; Tunable White (2700K-5700K)

CRI: 83 or 90+ typ. (2700K, 3000K, 3500K, 4000K)

90+ (Tunable White)

Static White Tunable White

Dimming (wired): 0-10V, 1% dimming (standard) 0-10V TW, 1% dimming

Lutron LDE1 Hi-lume® 1% Dim DALI DT8, 1% digital dimming

Lutron Athena TW (integral

wireless RF node)

Soft-On/Fade-to-Black DALI dimming, 1% dim

Dimming (wireless): Lutron Athena (integral

wireless RF node)

BubblyNet Bluetooth

Certifications







Fixture Summary

Performance Data

Nominal	Delivered Lumens				Color		
Wattage/Foot	Direct	Indirect	direct Total		Temp	CRI	
5/5	2343	2644	4987	133.7	3500K	83	
10/10	4401	4989	9390	126.9	3500K	83	

Data is based on 3500K-83120V IES files available on website.

Data is based on 4' fixture with Performance Lens direct and Upper Clear lens indirect.

Electrical Data

		4'		8'	
Wattage per Foot	Voltage	System Watts	Amps	System Watts	Amps
5	120V	37.3	0.31	74.6	0.62
0	277V	37.3	0.14	74.6	0.27
10	120V	74	0.62	148	1.23
10	277V	74	0.27	148	0.53

Electronic multi-volt (120-277VAC), constant current LED driver.

Standard Patterns

L					Wall to Ceiling	Custom*
Yes	Yes	Yes	Yes	Yes	No	Yes

^{*} Submit drawing, consult factory.

Runs

TYPE:

Individual Runs: 2' - 8' (whole foot standard).

Continuous Runs: Available (whole foot standard).

Custom: Made to measure lengths available (nearest 1/8" of field dimensions).

Requires approval drawings. Added cost & lead time.



Linear Direct/Indirect



PROJECT: TYPE:

Ordering Information

LIN3.5DI-A16. 120/277 11 8 10 12 Model Optics (select 1 from each list) Mounting 4 Circuiting LIN3.5DI-A16⁺ Pendant Mount (aircraft cable suspension) Wall Mount 1 single circuit Direct PL performance lens (standard) ASW04 through ceiling tile or gyp board, white, 4'* WM wall mount 2 up/down switch **DL** designer lens ASW10 through ceiling tile or gyp board, white, 10' separately SLDW straight blade louver, white aluminum, ASW20 through ceiling tile or gyp board, white, 20' solid blades w/overlay ASB04 through ceiling tile or gyp board, black, 4'* **SLDB** straight blade louver, black, solid blades ASB10 through ceiling tile or gyp board, black, 10' w/overlay ASB20 through ceiling tile or gyp board, black, 20' SLDS straight blade louver, silver, solid blades ASW04T over ceiling tee, white, 4'* w/overlav ASW10T over ceiling tee, white, 10' ASW20T over ceiling tee, white, 20' Indirect ASB04T over ceiling tee, black, 4'* ASB10T over ceiling tee, black, 10' BAT batwing uplight (standard) UC upper clear lens cover ASB20T over ceiling tee, black, 20' * 4' (xxx04) is standard length, other lengths are additional charge Wattage (per foot, D/I) 10/10 5/10

0,.0
10/5
Consult factory for othe
wattage options.
Note: 3' units must use
same wattage for D/I

Color Temp	
Static White	
27 2700K-83	279 2700K-90+
30 3000K-83	309 3000K-90+
35 3500K-83	359 3500K-90+
40 4000K-83	409 4000K-90+
Tunable White	
TW9-2757 tuna	able white, 90CRI

(2700K-5700K)

7	Finish
	HW high reflectance
	matte white
	BT black texture
	ST silver texture
	For other RAL color,
	consult factory

Voltage	9	Leng
120/277		
		Le
		- all p
		- IND
		- COI
		- CUS

Length		
Length A	() Length B	C Length C
- all patterns - IND - CON - CUS	- all patterns - PR (2 lengths of 2)	- PU - PZ

Configuration

components.

IND1 individual fixture, 2' to 8' in 1' increments

CON continuous run > than 8', specify to nearest foot CUS custom made to measure, +/- 1/8" of customer

supplied field dimensions

Standard Patterns (see pg 6 for details)

PLL L left, (2) straights + (1) 90° corner, leg right

PLR L right, (2) straights + (1) 90° corner, leg left

PU U shape, (3) straight lengths + (2) 90° corners

PR Rectangle shape, (4) straight lengths + (4) 90° corners

PZ Z shape, (3) straight lengths + (2) 90° corners

For custom patterns, submit an EDR on amerlux.com.

Drivers/Controls

Wired - Static White

0-10V 1% analogue dimming, 120-277VAC, dim to off when selected with wireless dimming control

HILUME-H-ECO Lutron LDE1 Hi-lume® 1% dim Soft-On/Fade-to-Black

DALI DALI dimming 120-277VAC. 1% dim

Wired - Tunable White

0-10V-TW 1% dimming, multi-volt (120V-277V) constant current

DALI-DT8 1% digital dimming, CCT control per DALI DT8 (120V-277V) constant current

Wireless - Static White

 $\textbf{AWNR-WH-SR} \ \, \text{Lutron Athena wireless node, RF only, white, D4i/DALI-2}$

AWNR-BL-SR Lutron Athena wireless node, RF only, black, D4i/DALI-2

AWNR-WH-010 Lutron Athena wireless node, RF only, white, O-10V

AWNR-BL-010 Lutron Athena wireless node, RF only, black, 0-10V

AWNR-OCC-WH-SR Lutron Athena wireless node, Occupancy & Daylight sensor, white, D4i/DALI-2

AWNR-OCC-BL-SR Lutron Athena wireless node, Occupancy & Daylight sensor, black, D4i/DALI-2

AWNR-OCC-WH-010 Lutron Athena wireless node, Occupancy & Daylight sensor, white, 0-10V

AWNR-OCC-BL-010 Lutron Athena wireless node, Occupancy & Daylight sensor, black, 0-10V BN-BT-OCC-WH-SR BubblyNet Bluetooth node, Occupancy & Daylight sensor, white, D4i/DALI-2

BN-BT-OCC-WH-010 BubblyNet Bluetooth node, Occupancy & Daylight sensor, white, 0-10V

Wireless - Tunable White

AWNR-WH-SR-TW Lutron Athena wireless node, RF only, white, D4i/DALI-2

AWNR-BL-SR-TW Lutron Athena wireless node, RF only, black, D4i/DALI-2

AWNR-OCC-WH-SR-TW Lutron Athena wireless node, Occupancy & Daylight sensor, white, D4i/DALI-2 AWNR-OCC-BL-SR-TW Lutron Athena wireless node, Occupancy & Daylight sensor, black, D4i/DALI-2

12 Options/Accessories

EMC-PF2 emergency circuit requires power feed located in last fixture section (for other locations consult factory)

PF² Extra power feed for additional circuiting

EMB⁺ emergency battery pack (not available for lengths under 4')

* An additional PF needs to be ordered for all 2-circuit DI fixtures ordered with an EMB.

² Not available with IND (individual) configuration



[†] The "A" refers to the sequential revision in a year and "XX" refers to the year of update. Updates coincide with improved performance while not changing the overall fixture aesthetic and are reflected in the published performance data. Please contact your Amerlux representative for explanations of changes

Lengths less than 4' may have restrictions based upon wattage, lengths, drivers or other options.



Specifications

Application

Open office plan, conference rooms, corridors or any indoor retail space where an exciting combination of direct and indirect ambient lighting is desired.

Construction

One piece extruded aluminum housing. Die-cast End Plates match fixture body finish. Die-formed, cold-rolled steel internal components are protected against rust and corrosion.

Optical

Direct:

All Direct lenses are snap-in, extruded acrylic, with a maximum length of 8". Amerlux's proprietary acrylic lens provides excellent transmission while effectively concealing source image.

PL - Performance Lens provides high efficiency with controlled lens surface brightness (standard).

 $\ensuremath{\text{DL}}$ - Designer Lens provides flat even glow on lens. Best when lens is in direct or constant view.

SLDx - Straight blade Louver Direct has 0.5" high blades 0.81" on center. Available in (*W*) white aluminum (*light gray, appears white when lit*), (*B*) black or (*S*) silver. Indirect:

Extruded acrylic lens with a maximum length of 8'.

BAT- Batwing uplight lens (standard) spreads light directly above fixture. A minimum of 18" distance between ceiling plane and top of fixture is suggested.

UC - Upper Clear lens cover (optional).

LED

Amerlux's boards and patented connector design with brand name LEDs enables Amerlux fixtures to have excellent thermal management and offer a 5 year warranty. Our LED binning is within 3 MacAdam ellipse. Boards are configured for maximum flexibility resulting in even illumination no matter what the fixture layout. LED boards are easily replaced in the field with just a Phillips screw driver.

	Static White	Tunable White
CCT:	2700K, 3000K, 3500K, 4000K	2700K-5700K
CRI:	83 or 90+ typical	90+ (92 typ)
R9:	16 @ CRI 83; >50 @ CRI 90+	>50

Life: 50,000+ hr., > 70% of initial lumens (L70)

Electrical

Wiring: Individual and "Beginning of Run" (BOR) fixtures are prewired with power cord. All configurations have quick connect power harnesses for row connections.

- 1 1 Circuit, direct & indirect same circuit
- **2** 2 Circuits, direct & indirect switch separately (power feed at both ends). Standard Wattage: 5W/ft, 10W/ft.

 $\label{thm:continuous} Optional\ Wattages: 3W/ft, 4W/ft, 6W/ft, 7W/ft, 8W/ft, 9W/ft. (3W \&\ 4W\ have\ a\ minium\ length\ of\ 4').$ For other wattages consult factory.

Emergency circuit via remote inverter or auxiliary emergency power supply (by others).

This product complies with IEEE C62.41 for surge endurance up to 2.5KV. Amerlux $^{\circ}$ recommends using additional surge protection with this unit (supplied by others), surge and over voltage damage is not covered under warranty.

EMC-PF - Emergency circuit requires power feed to be located in last fixture section for continuous runs. For other locations consult factory. Not available for individual (*IND*) configuration.

PF - Extra power feed for additional circuiting. Not available for individual (*IND*) configuration.

Finish

All painted surfaces are premium powder coated baked on for maximum durability and color stability.

HW - High reflective matte White

BT - Black Texture

ST - Silver Texture

For special paint colors supply RAL and/or actual paint chip for factory consultation.

Configurations/Lengths

IND - Individual fixtures are made of single standard lengths of 2' to 8' (in 1' increments). These are stand alone fixtures with matching End Caps, supplied with the mounting hardware. Lengths less than 4' may have restrictions based upon wattage, lengths, drivers or other options.

CON - Continuous runs, > 8' specified to nearest whole foot length in 1' increments. Runs made from standard lengths have End Caps at the beginning and end of run. Runs > 60' may require second power feed. Each Housing has factory installed alignment pins. Mating fixtures are easily aligned and joined. Wiring is made fast and positive with molded quick connectors.

CUS - Custom made to measure runs are made to nearest 1/8" of customer supplied field measurements or drawings. Custom lengths use the same hardware for hairline joining.

PXX- Standard Patterns consist of 90° corners with standard lengths (4' to 8' in 1' increments), continuous runs or made to measure lengths. Depending upon complexity of the pattern drawings may be required from the customer. If ordering please give overall lengths.

A'-B'-PLL - L Left - (1) 90° Corner (2) segments. Specify overall segments: A' & B' A'-B'-PLR - L Right - (1) 90° Corner (2) segments. Specify overall segments: A' & B' A'-B'-PR - Rectangle - (4) 90° Corners joining (4) segments. Specify overall segments: A' & B'

 ${\bf A'-B'-C'-PU}$ - U shape - (2) 90° Corners joining (3) segments. Specify overall segments: A', B', & C'

A'-B'-C'-PZ - Z shape - (2) 90° Corners joining (3) segments. Specify overall segments: A', B', & O'

See page 6 for layouts.

For custom patterns, submit EDR on amerlux.com.

Mounting

The Linea 3.5 Direct/Indirect is intended to be pendant or wall mounted in continuous rows. For indirect lighting Ameriux suggests 18" min from top of fixture to ceiling. Standard or custom patterns available.

 $\label{local-loc$

Cable Suspension: Cable is stranded stainless steel wire. All fittings are protected against rust and corrosion. Canopies are $5^{\circ} \times 1/4^{\circ}$ die formed painted steel. Adjustment mechanism allows for infinite height adjustment. Amerlux recommends the required feed and non-feed suspensions based upon length and electrical options. Options include: color of canopy and power cord (black or white), length 10' or 20', and mounting condition, in center of ceiling tile and in gypsum board ceiling (standard) i.e. ASW10. Or if canopy is installed on a grid Tee runner add. T i.e. ASW10T

LIN3.5DI-A16....WM - Direct Indirect Wall Mounted using steel cleat bracket attached to fixture housing and wall bracket with set screws. Two bracket assemblies are used for each length under 8'. A third center bracket may be recommended. J box required at feed locations.

Please note: 1 Circuit is standard, the direct & indirect are on the same circuit. 2 Circuits, direct & indirect switched separately with power feeds at both ends.

Options

EMB - Emergency battery pack - 10W output power, 90 min of illumination time, up to 1300 lm of initial light output. Illuminated test-switch/charging indicator light is provided. Wattage consumption by EM: 2.5W/ft (4ft fixture), 1.66W/ft (6ft fixture), 1.25W/ft (8ft fixture). Request can be made to light up 4ft section on 8ft unit.

Certifications

Approved to UL standards for damp locations as tested by CSA Intended for indoor use only

Warranty

Amerlux's 5 year limited warranty. Please consult Amerlux website for details.




Linear Direct/Indirect




PROJECT: TYPE:

Product Details

Pendant







Optional Louver






Wall Mount





Joining the Housings



Secure Fixtures/Joint:


Bend up reflector cutout panels as shown to expose joining hardware Reflector Cutout Panels Rectangular Cutouts

- 1. Through cutouts in reflectors, locate screws installed loosely in joining brackets.
- 2. Drive combo screw diagonally into hole in opposite hanger bracket. Drive second screw diagonally into hole in opposite hanger bracket. Tighten both screws to pull together & secure fixtures.
- 3. Rebend down reflector cutout panels.






Cable Kit Suspension - Ceiling or Gypsum Board (ASW04, ASW10, ASW20, ASB04, ASB10, ASB20)



Cat#	Length	Cord/Canopy	Application
ASW04	4'	white/white	ceiling tile/gypsum
ASW10	10'	white/white	ceiling tile/gypsum
ASW20	20'	white/white	ceiling tile/gypsum
ASB04	4'	black/black	ceiling tile/gypsum
ASB10	10'	black/black	ceiling tile/gypsum
ASB20	20'	black/black	ceiling tile/gypsum
ASW04T	4'	white/white	ceiling tee
ASW10T	10'	white/white	ceiling tee
ASW20T	20'	white/white	ceiling tee
ASB04T	4'	black/black	ceiling tee
ASB10T	10'	black/black	ceiling tee
ASB20T	20'	black/black	ceiling tee

Tee Grid or Screw Slot (ASW04T, ASW10T, ASW20T, ASB04T, ASB10T, ASB20T)





Optional Sensor/RF Node

Amerlux® has partnered with control companies to create building environments that are safer and smarter, than ever before. At the heart of our partnership is intelligent RF nodes and Smart Sensor, the most advanced digital wireless communication and sensors available today. Integrated into Amerlux products.

Minimum run length is 3' for wireless sensor and RF node.

INDIVIDUAL (MIN 3' LENGTH)



Linea 3.5" Patterns

Standard Patterns

All corners are standard 90°, standard length legs.

Use standard lengths: 4' min to 8' in 1 foot increments.


Continuous runs must be the same length in pairs for closed configuration.

Custom Patterns

Please provide drawings of your configuration.


Made to Measure: +/- 1/8", consult factory.

PC - custom pattern, please provide drawings and consult factory.



Butt Joint-Straight


Linea 3.5 Lens Mitered Lens




PLL - L Left, (2) straights + (1) 90° corner, leg right PLR - L Right, (2) straights + (1) 90° corner, leg left

Provide overall lengths: A' & B'


Nomenclature: A-B-PLL



PR - Closed Rectangle, (4) straight lengths + (4) 90° corners Provide overall lengths: A' & B' Nomenclature: A-B-PR



PU - Open U, (3) straight lengths + (2) 90° corners Provide overall lengths: A', B' & C' Nomenclature: A-B-C-PU



PZ - Open Z, (3) straight lengths + (2) 90° corners Provide overall lengths: A', B' & C' Nomenclature: A-B-C-PZ



Linear Direct/Indirect



PROJECT: TYPE:

Performance Data

Multiplying Factors: (Multiplying Factor is based on 3500K-83 120V IES file on website)


Wattage:								
Factor:	0.31	0.42	0.53	0.63	0.72	0.81	0.90	1.0

ССТ	CCT Factors:						
CRI	2700K	3000K	3500K	4000K	(@3500K)		
83	0.92	0.97	1.0	1.02	-		
90	0.81	0.84	0.86	0.89	0.86		

	Louver		
Finish:	SLV	BLK	
Factor:	1.0	0.65	

LINEA 3.5" PERFORMANCE LENS 10W 3500K 4FT

Total Watts: 38; Total Lumens: 4401 Source: 128 White LED's



LTL# 14664757.17 ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixt
0-40	2174	49.4
0-60	3585	81.4
0-90	4401	100.0
90-180	0	0.0

Efficacy (lumens/watt) = 115.1 lm/W


COEFFICIENTS OF UTILIZATION

RC		8	0	
RW	70	50	30	10
RCR				
0	119	119	119	119
1	109	105	100	97
2	100	92	85	80
3	91	81	73	67
4	84	72	64	57
5	77	65	56	50
6	72	59	50	44
7	67	53	45	39
8	62	49	41	35
9	58	45	37	32
10	55	42	34	29
Noto: Va	luon overno	and an W of	total luman a	utnut

Note: Values expressed as % of total lumen output delivered to the task surface.

LINEA 3.5" DESIGNER LENS 10W 3500K 4FT

Total Watts: 38; Total Lumens: 3383 Source: 128 White LED's



LTL# 14664757.18

ZONAL LUI	MEN SUMMARY
-	

Zone	Lumens	%Fixt		
0-40	1489	44.0		
0-60	2630	77.7		
0-90	3383	100.0		
90-180	0	0.0		
Efficacy (lumens/watt) = 88.5 lm/W				


COEFFICIENTS OF UTILIZATION

RC		8	0	
RW	70	50	30	10
RCR				
0	119	119	119	119
1	108	104	99	95
2	98	90	83	77
3	90	79	71	64
4	82	70	61	54
5	75	62	53	46
6	70	56	47	40
7	64	51	42	36
8	60	46	38	32
9	56	43	34	29
10	53	39	31	26

Note: Values expressed as % of total lumen output

LINEA 3.5" STRAIGHT BLADE LOUVER 10W 3500K 4FT

Total Watts: 38 Total Lumens: 2038 Source: 128 White LED's



LTL# 14664757.19

ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixt			
0-40	1188	58.3			
0-60	1835	90.0			
0-90	2038	100.0			
90-180	0	0.0			
Efficacy (lumens/watt) = 53.3 lm/W					

COEFFICIENTS OF UTILIZATION

RC		8	0	
RW	70	50	30	10
RCR				
0	119	119	119	119
1	111	107	103	100
2	102	95	90	85
3	95	86	79	73
4	88	78	69	63
5	81	70	62	56
6	75	63	55	50
7	70	58	50	45
8	66	53	46	40
9	62	49	42	37
10	58	46	38	34

Note: Values expressed as % of total lumen output

delivered to the task surface.







Performance Data (continued)


Multiplying Factors: (Multiplying Factor is based on 3500K-83 120V IES file on website)

Wattage:	3W	4W	5W	6W	7W	8W	9W	10W
Factor:	0.31	0.42	0.53	0.63	0.72	0.81	0.90	1.0

CCT	TW9				
CRI	2700K	3000K	3500K	4000K	(@3500K)
83	0.92	0.97	1.0	1.02	-
90	0.81	0.84	0.86	0.89	0.86

LINEA 3.5" INDIRECT BATWING 10W 3500K 4FT

Total Watts: 36; Total Lumens: 4653 Source: 120 White LED's



LTL#14626239.21A ZONAL LUMEN SUMMARY

Zone	Lumens	%Fixt
0-40	0	0.0
0-60	0	0.0
0-90	0	0.0
90-180	4653	100.0

Efficacy (lumens/watt) = 129 lm/W


COEFFICIENTS OF UTILIZATION

RC		8	0	
RW	70	50	30	10
RCR				
0	95	95	95	95
1	87	83	79	76
2	79	72	66	62
3	72	63	57	51
4	65	56	48	43
5	60	49	42	36
6	55	44	36	31
7	50	39	32	27
8	47	35	28	23
9	43	32	25	20
10	40	29	22	18
Motor Ma	luon overno	and an W oft	otal luman a	utnut

Note: Values expressed as % of total lumen output delivered to the task surface.

LINEA 3.5" INDIRECT UPPER CLEAR LENS 10W 3500K 4FT

Total Watts: 36; Total Lumens: 4989 Source: 120 White LED's



LTL# 14626239.20 **ZONAL LUMEN SUMMARY**

EOIT/LE EOITIEIT OOITIIT/TITT			
Zone	Lumens	%Fixt	
0-40	0	0.0	
0-60	0	0.0	
0-90	0	0.0	
90-180	4989	100.0	
Efficacy (lumens/watt) = 138.3 lm/W			

COEFFICIENTS OF UTILIZATION

RC		8	0	
RW	70	50	30	10
RCR				
0	95	95	95	95
1	87	83	79	76
2	79	72	66	62
3	72	63	57	51
4	65	56	48	43
5	60	49	42	36
6	55	44	36	31
7	50	39	32	27
8	47	35	28	23
9	43	32	25	20
10	40	29	22	18

Note: Values expressed as % of total lumen output delivered to the task surface.





Static White - Dimming Compatibility

Amerlux® Linea® fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (Dimmer, Fixture Quantity, Voltage, etc.) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---

0-10V Wiring Diagram

0-10V - DIMMING (Standard)

Integrates into a variety of building management and daylighting controls

Notes:

- 120V or 277V*
- · Dims down to 1% light output
- · Requires interface to turn off power to driver
- Consult Dimming manufacturer for installation instructions - DO NOT SHARE NEUTRALS!

o-10V Dimming Ground	Gray Purple Black	Driver 0-10V (-) 0-10V (+) Switched Hot	V+ Red
Neutral	White	Neutral Ground	V- Black

Compatible Dimmers†:			
Wall Box			Central System
Lutron:	Wattstopper:	Leviton:	Lutron Grafixk Eye with GRX-TV1 Interface
Diva - DVSTV	ADF-120277	Renoir II	
Maestro - MS-Z101			
Nova-T - NTSTV-DV			

LUTRON LDE1 DIMMING


Integrates into Lutron EcoSystem building management

Notes:

- 120VAC or 277VAC*
- Dims down to 1% Soft-On/Fade-to-Black
- EcoSystem Control
- Consult Dimming manufacturer for installation instructions - DO NOT SHARE NEUTRALS!

Compatible Dimmers [†] :	
Lutron ECO System	Central System
Pow Pak Dimming Modules	Lutron EcoSystem compatible controls
Energi Savr Node	
Grafik Eye QS/Homeworks	
QS Control Unit	
Quantum Hub	
Homeworks QS/My Room	

LDE1 (HILUME-H-ECO) EcoSystem Digital Control Wiring Diagram



- * Driver is 277VAC dimmable with appropriate dimmer (by others). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.
- † The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.





Static White - Dimming Compatibility (continued)

Amerlux® Linea® fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (*Dimmer, Fixture Quantity, Voltage, etc.*) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---

DALI - DALI DIMMING 120V-277V

Digital control protocol allows individual fixture control

Notes:


- 120VAC 277VAC*
- · Dims down to 1% light output in most cases

Compatible Dimmers [†] :		
Wall Box	Central System	
Leviton CD250 Controller	Dynalite	
	Fifth Light	

DALI Wiring Diagram DALI Bus DALI Purple Driver • Dimming Control Purple/WT Line Black Line <u>Neutr</u>al White Neutral Green Ground

Emergency Fixture with Built-In Battery Pack


Emergency fixture with built-in battery pack (*EMB*) wiring: Note: *EMB* not available on lengths under 4'.



- * Driver is 277VAC dimmable with appropriate dimmer (by others). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.
- † The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.



Tunable White




Tunable White range from 2700K-5700K, 90 CRI. See wiring diagrams below.

Tunable White - Dimming Compatibility


Amerlux® Linea® fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (*Dimmer, Fixture Quantity, Voltage, etc.*) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---


0-10V Wiring Diagram (Single Circuit)



0-10V Wiring Diagram (Dual Switch, Single Controls)



0-10V Wiring Diagram (Dual Circuit)



- * Driver is 277VAC dimmable with appropriate dimmer (by others). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.
- † The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.






Tunable White - Dimming Compatibility (continued)

Amerlux® Linea® fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (Dimmer, Fixture Quantity, Voltage, etc.) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---

DALI DT8 Wiring Diagram



^{*} Driver is 277VAC dimmable with appropriate dimmer (by others). All provided wiring diagrams show 120VAC wiring colors and method. Please refer to 277VAC dimmer installation instructions for 277VAC wiring diagrams.

[†] The absence of a dimmer from the lists above does not imply incompatibility. Please consult factory for compatibility inquiries.