

WARNING - RISK OF FIRE AND ELECTRICAL SHOCK. FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY. FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL SPECIFICATIONS. DISCONNECT POWER AT ELECTRICAL PANEL BEFORE SERVICING.

RETAIN THESE INSTRUCTIONS FOR MAINTENANCE REFERENCE.

TO ADJUST FIXTURE HEIGHT

1. LOOSEN (DON'T REMOVE) FLAT HEAD SCREW ON BOTTOM OF HOUSING
2. REMOVE COVER (AND FLAT HEAD SCREW) FROM HOUSING
3. LOOSEN (DON'T REMOVE) STRAIN RELIEF CAP
4. ADJUST POWER CORD LENGTH
5. IF NECESSARY, CUT, STRIP, AND RE-WIRE POWER CORD TO TRACK ADAPTER WIRES AND HOUSING GROUND WIRE
6. REVERSE STEPS 1-3 BY TIGHTENING STRAIN RELIEF CAP, REPLACING COVER (AND FLAT HEAD SCREW), THEN TIGHTENING FLAT HEAD SCREW

