D730ARP Series

LED Luminaire

PROJECT:	TYPE:

Features

The D730ARP Series is a high performance luminaire designed around an efficient Type III *(T3)* or Type V *(T5)* refractive lens, surrounded by a decorative cage with a choice of cast aluminum fitters. An available perforated light reflector can help minimize light to the upper hemisphere. Powered by the Amerlux patented AVISTA® LED system with options for intensity, distribution and color.

D73xARP

Product Overview

Wattage:	up to 86W
Lumen Output :	up to 10,943 lm; up to 143 lm/W
Color Temp:	2700K, 3000K, 4000K
	1900K *(Nightscape)*
Dimming:	0-10V dimming
	Manual onboard dimming option available

Certifications

5 year limited warranty AMERLUX LED

POWDER COATED TOUGH™

Electrostatic sensitive device, observe precautions for handling

Fixture Summary

Installation:
The luminaire will mount to a 3" OD post or tenon with 5/16" black oxide coated stainless steel set screws to ensure a solid connection. The diffuser will be held to the fitter by *(4)* 5/16"-18 black oxide coated stainless steel set screws.

Electrical:
- Over voltage and short circuit protected driver
- Series connected 10kV/20kA surge protector
- Automatic AC incoming voltage sensing *(120V–277V)*
- 347V/480V option consult factory
- 0-10V dimming
- Optional Socket only version available, consult factory

Diffuser Choices:
- Acrylic Type III
- Acrylic Type V

CCT, CRI:
- 2700K, 80CRI
- 3000K, 70CRI
- 4000K, 70CRI
- 1900K, 52CRI *(Nightscape, see pg 4)*

Power Level:
(see performance chart for output)
- 30W
- 44W
- 60W
- 86W

L70:
72,000+ hrs.

Finish:
Durable thermoset polyester powdercoat finish in the following:
- Satin Black
- Classic Bronze
- Gloss Textured Bronze
- Green
- Gloss Textured Black
- Textured Black
- Gloss Textured Green

Accessories:
- Solid Light Lid, aluminum reflector
- Dusk-to-dawn button type photocell
- Optional onboard field selectable output switch for dimming

ETL listed, suitable for wet locations.

D730ARP Series

LED Luminaire

amerlux

PROJECT:	TYPE:

Ordering Information

_____ . _____ . AVI-G3-SY . _____ . _____ . _____ . _____

1 2 3 4 5 6 7

1	Model
	D731ARP
	D734ARP
	D735ARP
	D736ARP

2	Diffuser Material - Distribution
	AC-T3 acrylic, type III
	AC-T5 acrylic, type V

3	LED System
	AVI-G3-SY Avista light engine with symmetrical distribution

4	CCT
	27 2700K
	30 3000K
	40 4000K
	NS 1900K *(Nightscape, see pg 4 for details)*

5	Power Level
	P1 *(30W)*
	P2 *(44W)*
	P3 *(60W)*
	P4 *(86W)*
	120V-277V auto-sensing driver is standard. Consult factory for 347V/480V option.

6	Finish
	BLK satin black
	CLB classic bronze
	GBZ gloss textured bronze
	GRN green
	GTB gloss textured black
	TBK textured black
	TGR gloss textured green
	CSTM custom

7	Accessories
	SLL solid light lid, aluminum reflector *(not available for use with 7IR)*
	PCL dusk-to-dawn button type photocell *(not available for use with 7IR)*
	7IR light engine integrated 7-pin NEMA receptacle *(to allow installation of a wireless control node for operation on the SmartSite or other control platform, not available for use with SLL, PCL or FSO)*
	FSO field selectable output option to allow manual dimming *(not available for use with CCH ro 7IR)*

***Please Note**: Fixture is available with optional Medium base (MDO) or Mogul base (MGO) socket only. Consult factory for details.*

Product Details



D731ARP
EPA: 2.02



D735ARP
EPA: 1.92



D734ARP
EPA: 2.15



D736ARP
EPA: 1.97

Avista Light Engine



AVI-G3
Weight: 6.2 - 6.6 lbs*

* Weight varies with Power ouput due to variances of the driver.

D730ARP Series

LED Luminaire

PROJECT:	TYPE:

Performance Data - Engine Only

Multiplying Factors: *(Multiplying Factor is based on 3000K IES file on website)*

CCT:	1900K (NS)	2700K	3000K	4000K
Factor:	0.85	0.91	1.0	1.05

Model	CCT	Power Level	System Watts	LED Engine Lumens	LED Engine LPW
AVI-G3 -SY	27	P1	30	3651	122.9
	30			4034	135.8
	40			4246	143.0
	NS			3445	116.0
	27	P2	44	5245	119.2
	30			5794	131.7
	40			6099	138.6
	NS			4948	113.0
	27	P3	60	7026	116.1
	30			7762	128.3
	40			8170	135.0
	NS			6628	110.0
	27	P4	86	9411	109.4
	30			10394	120.9
	40			10943	127.2
	NS			8878	104.0

Approximate lumens delivered from raw light engine.

Typical Light Distribution



T3 Diffuser



T5 Diffuser

D730ARP Series

LED Luminaire

PROJECT:	TYPE:

Spectral Power Distribution



Nightscape *(NS)* Technology

- Unique spectral distribution that delivers highest flux while emitting <2% light of blue.
- The Nightscape *(low blue)* Avista is powered by Luxeon 3030 HE Plus which delivers high efficacy and superior life span.