

SPEQ-S Kicker Wall Wash

Small Track Head



PROJECT:

TYPE:

Features

Bring attention, reveal rich textures and bring out the truest colors on wall mounted artwork and merchandise with the architecturally styled SPEQ Kicker Wall Wash. Ideal for murals, galleries and commercial lobby applications, the newest addition to the SPEQ architectural track head family complements its clean aesthetic and provides dramatic wall washing down walls with a uniform look. The fixture features a cut front snoot and kick optics, has no visible heat sink or venting, and the integral driver is fully featured, with low-end dimming and full 2.5 KV surge protection. For the perfect blend of exceptional aesthetics, optical performance and superior output, look no further than Amerlux's expanding SPEQ family.



SPEQ-S-KWW

Product Overview

Type: Track Wall Wash
Wattage: 9W, 15W
Color Temp: 2200K, 2700K, 3000K, 3500K, 4000K
CRI: 83 typ. (2700K, 3000K, 3500K, 4000K)
90+ typ. (2200K, 2700K, 3000K, 3500K, 4000K)
3K Class A LED's available
Dimming: TRIAC & ELV, 5% Dim, 120VAC

Certifications



Fixture Summary

Performance Data

Watts	Delivered Lumens	LPW	Color Temp-CRI
9	493	54.8	3000K-83
15	822	52.1	3000K-83

Data is based on 3000K-83 120V IES files available on website.

Electrical Data

	9W		15W	
Voltage	System Watts	Amps	System Watts	Amps
120V	9	0.08	15	0.13

Electronic constant current LED driver.

SPEQ-S Kicker Wall Wash

Small Track Head



PROJECT:

TYPE:

Ordering Information

SPEQ-S-KWW		120		LE/TE			
1	2	3	4	5	6	7	
1	Model	2	Wattage	3	Finish	4	Mounting
	SPEQ-S-KWW	9		WT	white texture	TN1	Global GES /H-Style, 1 circuit, 120V
		15		BT	black texture	TEK	Global TEK 2 circuit/ 2 neutral, 120V
				ST	silver texture	TN3	Global XTS 3 circuit, 120V
				Other finishes, consult factory		CT	J-Style 1 or 2 circuit, 120V
						LOL	L-Style 1 circuit, 120V
						C	canopy, 120V
						CCL2-SCP	C-clamp, black, with straight cord*, 6' 120V
						CCL2-CCP	C-clamp, black, with coil cord*, 5' 120V
Notes: * Black cord used for BT & ST finish. White cord used for WT finish.							
5	Voltage	6	Color Temp	7	Driver		
	120	83 CRI	90+ CRI		LE/TE	TRIAC/ELV dimming	
		27 2700K-83	229 2200K-90+	3CLA 3K Class A			
		30 3000K-83	279 2700K-90+				
		35 3500K-83	309 3000K-90+				
		40 4000K-83	359 3500K-90+				
			409 4000K-90+				

SPEQ-S Kicker Wall Wash

Small Track Head



PROJECT:

TYPE:

Specifications

Application

Retail, Museum, Gallery, Hospitality and Commercial accent and display lighting

Construction

Complete die-cast aluminum construction
No exposed wiring
Unique magnetic dual lock front door

Optical

Amerlux Designed TIR optical system
0-90° tilt, 360° rotation
Tilt indicating marks for common tilt positioning
Kicker Wall Wash optics

LED

Color Temp Options: 2200K, 2700K, 3000K, 3500K, 4000K
CRI: 83 typ. (2700K, 3000K, 3500K, 4000K)
90+ typ. (2200K, 2700K, 3000K, 3500K, 4000K)
Class A* 3000K LEDs available

R9 Values: 11 (83 CRI), 55 (90+ CRI)

Binning: 3-step MacAdam ellipse (SDCM)

Life: 50,000+ hrs, > 70% of initial lumens at 50,000 hrs

** Class A LED: Class A LED's have a CRI > 80 and a GAI > 80. CRI defines color "Naturalness" and GAI defines color "Saturation." Both being high delivers rich colors and pure whites.*

Electrical

Wattage: 9W, 15W

Electronic constant current LED driver, 120VAC input

This product complies with IEEE C62.41 for surge endurance up to 2.5KV. Amerlux® recommends using additional surge protection with this unit (supplied by others), surge and over voltage damage is not covered under warranty.

Driver

LE/TE - Leading Edge (Triac, Forward Phase) or Trailing Edge (ELV, Reverse Phase) autosensing driver dims down to 5% on most dimming systems.

Driver rated for A/C voltage input +/- 10%

See dimming page for more information.

Finish

Powder coat paint.

Standard Colors: White Texture, Black Texture, Silver Texture

Consult factory for custom RAL powder coat finishes

Mounting

Track, canopy and c-clamp.

Note: Recommend track fixture mounting to horizontal surface mounted/pendant mounted track only

Certifications

Approved to UL standards as tested by CSA.

Intended for indoor use only.

Warranty

5 year limited warranty



SPEQ-S Kicker Wall Wash


Small Track Head




PROJECT:

TYPE:


Product Details



TEK/TN3 Track Adapter



Canopy Mount



SPEQ-S Kicker Wall Wash

Small Track Head



PROJECT:

TYPE:

Performance Data

Multiplying Factors: (Multiplying Factor is based on 3000K-83 120V IES file on website)


CCT:	2700K-83	3000K-83	3500K-83	4000K-83
Factor:	0.96	1.0	1.02	1.04

Wattage:	9W	15W
Factor:	0.60	1.0

CCT:	2200K-90+	2700K-90+	3000K-90+	3500K-90+	4000K-90+	3CLA
Factor:	0.71	0.80	0.83	0.87	0.90	0.75

15W LED, 3000K KWW

Kicker Wall Wash
LTL # 14087258.01
Lumens: 822



Zonal Lumen Summary

Zone	Lumens	%Fixt
0-40	613	74.6
0-60	796	96.8
0-90	820	99.8
90-180	2	0.2

Luminaire Efficacy: 52.1 lm/W

Application Data

Single Fixture
3' off wall

Distance from ceiling	0.5'	0	0	1	1	1	1	1	1	0	0
1.5'	0	1	1	3	14	14	3	1	1	0	0
2.5'	1	1	3	13	36	36	13	3	1	1	1
3.5'	1	2	6	16	25	25	16	6	2	1	1
4.5'	1	3	7	11	14	14	11	7	3	1	1
5.5'	2	3	5	7	8	8	7	5	3	2	2
6.5'	2	3	4	5	5	5	5	4	3	2	2
7.5'	2	2	3	3	4	4	3	3	2	2	2
8.5'	2	2	2	3	3	3	3	2	2	2	2

Multiple Fixtures
3' off wall; 2.5' oc

Distance from ceiling	0.5'	2	3	4	3	4	4	4	4	4	4	4	4	4	4	4	3	4	3	2
1.5'	4	10	23	12	18	18	12	24	12	18	18	12	24	12	18	18	12	23	10	4
2.5'	9	28	46	40	45	45	41	49	41	45	45	41	49	41	45	45	40	46	28	9
3.5'	15	26	35	40	40	40	41	41	41	41	41	41	41	41	40	40	40	35	26	15
4.5'	14	19	24	28	29	30	30	31	30	30	30	30	31	30	30	29	28	24	19	14
5.5'	12	14	17	19	21	22	22	23	22	22	22	22	23	22	22	21	19	17	14	12
6.5'	10	11	13	14	15	16	17	17	17	17	17	17	17	17	16	15	14	13	11	10
7.5'	8	9	10	11	12	13	13	14	14	14	14	14	14	14	13	13	12	11	10	8
8.5'	7	8	9	9	10	11	11	12	12	12	12	12	12	12	11	11	10	9	8	7

SPEQ-S Kicker Wall Wash

Small Track Head



PROJECT:

TYPE:

Dimming Compatibility

Amerlux® SPEQ® fixtures are compatible with all major dimming protocols prevalent in the United States. Please see below for general compatibilities and wiring diagrams. Amerlux recommends testing your unique dimming configuration as the exact full configuration (*Dimmer, Fixture Quantity, Voltage, etc*) may affect dimming performance.

--- NOTE: INFORMATION BELOW IS FOR WIRED DIMMERS ONLY. FOR WIRELESS DIMMERS, CONSULT FACTORY ---


TRIAC (Forward Phase) Dimming (Standard)

Utilizes standard TRIAC dimmers that are in wide use in installations across the US. Best for retrofit applications where TRIAC dimmers are installed.

Notes:

- 120VAC only
- Dims down to 5% light output (*most cases*)
- Consult Dimming manufacturer for installation instructions - **DO NOT SHARE NEUTRALS!**
- Must meet dimmer Minimum Load Requirements per dimming manufacturer

TRIAC Wiring Diagram



Compatible Dimmers*:

Wall Box (TRIAC 120VAC)

Lutron "Diva"

Lutron "Nova-T"

Lutron "Maestro"

Lutron "Skylark"


ELV - Electronic Low Voltage (Reverse Phase) Dimming (Standard)

Utilizes specialized "ELV" dimmers.

Notes:

- 120VAC only
- Dims down to 5% light output (*most cases*)
- Consult Dimming manufacturer for installation instructions - **DO NOT SHARE NEUTRALS!**
- Must meet dimmer Minimum Load Requirements per dimming manufacturer

ELV Wiring Diagram



Compatible Dimmers*:

Wall Box (ELV 120VAC)

Lutron "Diva"

Lutron "Nova-T"

Lutron "Maestro"

Lutron "Skylark"

Leviton "Surslide"

Leviton "Vizio"