

DU730ARP Series

Utility LED Luminaire



PROJECT:

TYPE:

Features

Decorative lighting for residential roadway and commercial property, where independent fixture control is desired. The DU730ARP Series consists of an efficient Type III (T3) or Type V (T5) refractive acorn combined with one of several styles of cast aluminum fitters. Powered by the Amerlux patented AVISTA® LED system with options for intensity, distribution and color.

Product Overview

Wattage: up to 86W
Lumen Output: up to 10,943 lm; up to 143 lm/W
Color Temp: 2700K, 3000K, 4000K
Dimming: 0-10V dimming
Manual onboard dimming option available



DU730ARP-Fxx

Certifications



Fixture Summary

Installation:

The luminaire will mount to a 3" OD post or tenon with 5/16" black oxide coated stainless steel set screws to ensure a solid connection. The diffuser will be held to the fitter by (4) 5/16"-18 square head, black oxide coated stainless steel set screws.

Electrical:

- Over voltage and short circuit protected driver
- Series connected 10kV/20kA surge protector
- Automatic AC incoming voltage sensing (120V-277V)
- 347V/480V option consult factory
- 0-10V dimming
- 7 pin twistlock receptacle included (*photocell optional*)
- Optional 3 pin twistlock receptacle available, consult factory
- Optional Socket only version available, consult factory

Diffuser Choices:

- Acrylic Type III
- Acrylic Type V

CCT, CRI:

- 2700K, 80CRI
- 3000K, 70CRI
- 4000K, 70CRI

Power Level:

(see performance chart for output)

- 30W
- 44W
- 60W
- 86W

L70:

72,000+ hrs.

Finish:

Durable thermoset polyester powdercoat finish in the following:

- Satin Black
- Classic Bronze
- Gloss Textured Bronze
- Green
- Gloss Textured Black
- Textured Black
- Gloss Textured Green

Accessories:

- Twistlock photocell
- Optional onboard field selectable output switch for dimming

ETL listed, suitable for wet locations.

DU730ARP Series

Utility LED Luminaire



PROJECT:


TYPE:

Ordering Information


AVI-G3-SY						
1	2	3	4	5	6	7
1 Model	2 Diffuser Material - Distribution	3 LED System	4 Light Distribution	5 Power Level	6 Finish	7 Accessories
DU730ARP-F1 DU730ARP-F4 DU730ARP-F34 DU730ARP-F37	AC-T3 acrylic type III AC-T5 acrylic type V	AVI-G3-SY Avista light engine with symmetrical distribution	27 2700K 30 3000K 40 4000K	P1 30W P2 44W P3 60W P4 86W 120V-277V auto-sensing driver is standard. Consult factory for 347V/480V option.	BLK satin black CLB classic bronze GBZ gloss textured bronze GRN green GTB gloss textured black TBK textured black TGR gloss textured green CSTM custom	TW-PCL twistlock photocell 3PIN 3-pin twistlock receptacle FSO field selectable output (to allow manual dimming, not available for use with the standard 7 pin receptacle) <i>Note: All fitters include a 7-pin twistlock receptacle and an access door with window for the photocell. The photocell device is optional.</i>

Please Note: Fixture is available with optional Medium base (MDO) or Mogul base (MGO) socket only. Consult factory for details.

Product Details



Avista Light Engine



AVI-G3

Weight: 6.2 - 6.6 lbs*

* Weight varies with Power output due to variances of the driver.



DU730ARP Series

Utility LED Luminaire



PROJECT:

TYPE:

Performance Data - Engine Only


Multiplying Factors: (Multiplying Factor is based on 3000K IES file on website)

CCT:	2700K	3000K	4000K
Factor:	0.91	1.0	1.05


Model	CCT	Power Level	System Watts	LED Engine Lumens	LED Engine LPW
AVI-G3-SY	27	P1	30	3651	122.9
	30			4034	135.8
	40			4246	143.0
	27	P2	44	5245	119.2
	30			5794	131.7
	40			6099	138.6
	27	P3	60	7026	116.1
	30			7762	128.3
	40			8170	135.0
	27	P4	86	9411	109.4
	30			10394	120.9
	40			10943	127.2

Approximate lumens delivered from raw light engine.

Typical Light Distribution



T3 Diffuser



T5 Diffuser

Spectral Power Distribution

